

ORACRS

HIGH SPEED OVEN - ALL IN ONE. COMBI WAVE / HIGH SPEED OVEN - STANDARD VERSION (COLOR RED. RAL 3020)



 *High Speed Oven*  *Combi Wave*

Features



HIGH SPEED OVEN

An operating mode that simultaneously uses convection, microwave and impingement modes, with temperatures from 100°C to 300°C [212°F to 572°F].



COMBI WAVE

In Combi Wave mode, the high speed oven can be used as a convection oven with temperatures from 30°C to 300°C [86°F to 572°F], as a microwave oven with power up to 2000W or with a combination of the two cooking methods to achieve results that always exceed expectations.



CONNECTED

Oracle connects free-of-charge to Lainox's Nabook plus portal via the standard- supply Wi-Fi and ethernet features giving you a 4.0 kitchen (find out more on nabookplus.cloud).



OOS - ORACLE ODORLESS SYSTEM

A labyrinth baffle catalyst filter containing platinum particles which help to reduce steam, odours and grease residue during cooking. The Oracle Odorless System does not require any cleaning or routine maintenance work. Its efficiency is always guaranteed.



FAST COOKING SYSTEM

Rely on our know-how with automatic, tried-and-tested recipes for high-speed cooking in High Speed Oven mode.



MICROWAVE COOKING SYSTEM

Rely on our know-how by using the automatic, tried-and-tested recipes for cooking in Combi Wave mode.



OWB - ORACLE WASHABLE BOX

A special Teflon oven chamber which can be removed and washed for the next round of cooking, making the cleaning procedure fast and cost-effective.



Conforms to: UL STD 923
Cert. to: CSA STD C22.2 No. 150



Conforms to: NSF4



Capacity				
Capacity	17,9 lt.			
Dimensions				
Width	mm	467	inch	18.4
Depth	mm	609	inch	24.0
Height	mm	630	inch	24.8
Maximum outer width	mm	467	inch	18.4
Max exterior depth	mm	657	inch	25.9
Maximum exterior height	mm	630	inch	24.8
Packaging width	mm	600	inch	23.6
Packing depth	mm	800	inch	31.5
Packaging height	mm	800	inch	31.5
Weight	kg	61	lbs	134.5
Gross weight	kg	73	lbs	161.0
Volume	m3	0.18	ft3	6.4
Packing volume	m3	0.384	ft3	13.6
Cooking compartment width	mm	310	inch	12.2
Cooking compartment depth	mm	320	inch	12.6
Cooking chamber dimensions	mm	180	inch	7.1
Support base width	mm	426	inch	16.8
Base dimensions	mm	510	inch	20.1
Power plug configuration	Nema 6-20P			
Cable length	m	1.83	ft	6.00
Technical Data				
High Speed Oven temperature	°C	100 / 300 [212 / 572 °F]	°F	NaN
Temperatura Combi Wave	°C	30 / 300 [86 / 572 °F]	°F	NaN
Power supply				
Power supply voltage	2P AC 208 V			
Consumption	A	13,5		
Frequency	Hz	60		
Total electric power	kW	3		
Microwave	kW	1		
Impingement	kW	3		

Emissions	
Latent heat	W 435
Sensitive heat	W 271
Noisiness	db < 70

OPTIONAL ELECTRIC CONFIGURATION, WITHOUT EXTRA CHARGE - TO BE REQUESTED WHEN ORDERING

Option code	Connection plug	Cable length	Power supply voltage	Frequency	Total electric power		Power output - kW		Country		
	(Plug provided)	(Provided - mt.)		Hz	kW	A	Impingement	Microwave			
OR620U	NEMA 6-20	1,83	2P AC 240 V	60	3,3	13,5	3	1			
AUS	Australia	EU	Europe	KO	South Korea	KSA	Kingdom of Saudi Arabia	LATAM	Latin America	UK	United Kingdom

HOW TO USE

- Combi Wave. - MCS (Microwave Cooking System) automatic cooking system for Italian and international recipes, including the history, ingredients, cooking accessories, procedure and automatic cooking program. - Manual mode with three instant start cooking methods: convection, microwave or combined convection + microwave.
- High Speed Oven. - FCS (Fast Cooking System) automatic cooking system for Italian and international recipes, including the history, ingredients, cooking accessories, method and automatic cooking program. - Manual mode with instant start.
- Programmable mode: possibility of programming and storing a recipe with its cooking procedures in automatic sequence.

CONNECTIVITY

- Nabook Plus - Thanks to the Cloud feature, it is possible to access Nabook Plus, the virtual kitchen assistant (read more on nabookplus.cloud, free registration).
- Direct access to the recipe database with download option (patented).
- Synchronisation of multiple Oracle ovens connected to the same account (patented).
- HACCP monitoring.
- Remote diagnosis via Nabook plus portal by Lainox Service Centers.
- Possibility to download recipes from the Nabook Plus portal based on country.
- Possibility to run automatic software updates on multiple devices simultaneously.
- Wi-Fi connection. Compatible with IEEE 802.11g (2.4 GHz) standard.
- Automatic software update notification system.
- Recipe creation including ingredients with procedure and photo.

CONTROL MECHANISMS

- USB connection to download HACCP data, update software and upload/download cooking recipes.
- Possibility of choosing the fan speed.
- Automatic fan speed for High Speed Oven mode.

STRUCTURAL CHARACTERISTICS

- Pull-down door with ergonomic handle.
- When open, the door slides under the cooking surface of the oven, allowing the food to be removed safely without the risk of burns.
- Integrated catalyst filter for operation without hood.
- Perfectly smooth room.

OPERATION

- 7" colour screen (LCD, high definition, capacitive, with "Touch Screen" functions).
- Organisation of recipes in folders with preview, giving each folder its own name.
- Display that can be configured based on the user's needs, bringing forward the programmes used most.
- Oracle coach. Virtual assistant that provides advice on using and informs when maintenance is needed.
- There are about 30 recipes available in Oracle and a growing number of alternative ones are available via access to the Nabook plus portal. Each recipe has been tested to guarantee best results.
- Rapid cooling of the cooking chamber with open door.
- Possibility of preheating the cooking chamber up to 300°C [572°F] .
- Starting an automatic "One Touch" cooking.
- User interface with a choice of 29 languages.

SAFETY FEATURES

- Self-diagnosis with smart error viewing.
- Door open/closed electronic sensor.
- Compliant with the IEC60335-1, IEC60335-2-90 and EMC international standards.
- Maximum external door front temperature of 65°C [149°F].

CLEANING AND MAINTENANCE

- Easy exterior cleaning thanks to perfectly smooth surfaces, and IPX3 water jet protection rating.
- OWB - Oracle Washable Box. Special removable and washable box chamber.

INSTALLATION AND ENVIRONMENT

- Quality ISO 9001 / Safety ISO 45001 / Environmental ISO 14001 certification.
- Product recycling rate: 90%.
- 100% recyclable packaging.

STANDARD EQUIPMENT

- Ethernet connection
- Aluminium peel (190 x 330 x 50 mm)
- Oracle Washable Door Cover. Removable and washable inner door protection
- Oracle Washable Box
- Anodized aluminum alloy plate
- Wi-Fi connection. Compatible with IEEE 802.11g (2.4GHz) standard
- USB connection
- Power cable - 6 ft
- Electric plug - only for 2P version


OPTIONAL TO BE REQUESTED WHEN ORDERING

MPACK: Multipack packaging - 6 pcs mixed in a single package - 1200 x 800 x 2170 h - 415 kg - 2,08 m3. Not compatible with optional SOPPRS

SOWBHD: Extra charge for Oracle Washable Box Heavy Duty version OWBHD. Replaces the standard model

SOPPRS: Panini Stone Press kit (consisting of Panini Stone Press OPPRS - dedicated Oracle Washable Box OWBPRS - special paddle OPFAPRS) + preparation on the oven. Oracle Washable Box standard excluded from standard equipment. Not compatible with MPACK multipack packaging

OR620U: Optional electric configuration, without extra charge. 2P AC 208 V - 60 Hz. Plug included (NEMA 6-20)



A	Technical compartment cooling air intake	E	Electric power supply cable inlet	USB connection	Ethernet connection
---	--	---	-----------------------------------	----------------	---------------------

The data reported in this document is to be considered non-binding. The company reserves the right to make changes at any time, without prior notice